

/ Technical Data*

Metrics

Width	120 cm*	145 cm	210 cm	250 cm
Length	155 cm	155 cm	155 cm	155 cm
Height	38 cm	38 cm	38 cm	38 cm

Weight

Total	84 kg	89 kg	99,5 kg	106,5 kg
Central unit	17 kg	17 kg	17 kg	17 kg
Chassis	31 kg	31 kg	32,5 kg	33,5 kg
Brush unit	2 x 18,5 kg	2 x 20,5 kg	2 x 25 kg	2 x 28 kg
Load calculation	3.820Pa	3.910 Pa	4.160 Pa	4.330 Pa

Operation

Maximum speed	25 m/min	25 m/min	25 m/min	25 m/min
Cleaning speed	1.470 m ² /h	1.940 m ² /h	2.790 m ² /h	3.320 m ² /h
Max. inclination of solar modules	30°*	30°*	25°	20°
Water supply	0-600 l/h 2-4 bar	0-600 l/h 2-4 bar	0-600 l/h 2-4 bar	0-600 l/h 2-4 bar
Brush rotation	200 rpm	200 rpm	200 rpm	200 rpm

* 30° inclination, with ideal conditions for the system and a trained driver.
The machine must be secured.

Extras

Modular architecture
Warning system for low battery
Maintenance package for small repairs on site
Protection class for motors (imperviousness) IP 65
Splash guards for additional protection of motors
Adjustable water flow



Contact

sales@suntex.energy
+49 (0) 8332 243 43 - 30
www.suntex.energy

suntex GmbH

Am Bahnhof 14
87760 Lachen